

DocuPrint P225 d / P265 dw / M225 dw / M225 z / M265 z A4 Monochrome Printers

Delivering performance and productivity with clever connectivity



Powerful, efficient performers

The Fuji Xerox DocuPrint P225 d / P265 dw / M225 dw / M225 z / M265 z are the perfect solution for personal use or small offices requiring high quality, efficient monochrome printing together with flexible connectivity capabilities.

Performance and reliability

- Speed and quality. With a print resolution of up to 2400 x 600 dpi and a printing speed of up to 30 ppm, the DocuPrint P225 d / P265 dw / M225 dw / M225 z / M265 z deliver quality print results fast.
- All-in-one functionality. Multifunction models allow you to print, copy, scan and fax* in an efficient, low cost device giving you maximum productivity.
- Clever features for reliable operation.
 Fuji Xerox is renowned for reliable printing.
 The DocuPrint P225 d / P265 dw / M225 dw / M225 z / M265 z are no exception with simple engineering and clever new ideas designed for trouble-free printing.

*Only available on DocuPrint M225 z / M265 z

Affordable, efficient printing

- Low cost hardware is only half of the story. Thanks to the separate toner and drum cartridge, you will only ever have to replace one component at a time. This results in maximum use of each component, longer operating times and cost savings.
- Save toner save cost. Toner save mode extends the life of the toner cartridge by varying the density of toner that is printed on a page.
- Use less paper and toner. The built in N-UP print feature gives users the ability to save on paper and toner by printing multiple pages on a single sheet of paper. This also reduces the overall cost of printing.



Easily connect and print via your iOS or Android devices

AirPrint and Google Cloud Print Ready



AirPrint™ and Google Cloud Print™ enables you to print directly from your mobile device without the need to download mobile apps or to install print drivers.





Print Utility



Whether it's an iOS or Android device, the Fuji Xerox Print Utility puts mobile printing at your fingertips. Print stored photo albums, web pages or shoot and print on the go from your iOS or Android device.

Fuji Xerox Print Utility can be easily downloaded from the App Store for iOS and Play Store for Android devices.









Print from anywhere. Google Cloud Print allows you to connect your printers to the web, so you can make your home and work printers available to you from the applications you use every day, from wherever you are.

DocuPrint M265 z 4-in-1 Multifunction Laser Printer



Smart features increase productivity

2.7" Colour Touch Screen*



The 2.7" colour touch screen available on the DocuPrint M265 z provides a clear, simple user inteface that makes walk up functions easy to access.

Duplex printing as standard

Enjoy increased productivity and cost savings with Duplex printing as standard across the entire printer lineup.

The DocuPrint M265 z also features a Duplex Automatic Document Feeder (DADF) supporting duplex scanning and copying, delivering efficiency and productivity gains to any workspace.

Clever ID Card Copying*

The easy-to-use ID card copy feature allows you to copy both sides of the card onto the same side of the paper. Simply place an ID card both face up & down on the copier surface, pressing the start button each time. There is no need to change the position of the cards when copying the other side, as the feature automatically adjusts this for you.







*Available on multifunction models



DocuPrint P225 d Laser Printer



DocuPrint P265 dw Wireless Laser Printer



DocuPrint M225 dw 3-in-1 Wireless Multifunction Laser Printer



DocuPrint M225 z 4-in-1 Wireless Multifunction Laser Printer



DocuPrint M265 z 4-in-1 Wireless Multifunction Laser Printer

DocuPrint P225 d / P265 dw / M225 dw / M225 z / M265 z Specifications

Product Name	DocuPrint P225 d	DocuPrint P265 dw	DocuPrint M225 dw	DocuPrint M225 z	DocuPrint M265 z	
unction	A4 monochr	ome printer		A4 monochrome MFP		
rint Function rint Speed (A4)	Up to 26 ppm ¹	Up to 30 ppm ¹	Un to 261	Up to 26 ppm ¹	Up to 30 ppm ¹	
rint Resolution	<u> </u>	Up to 30 ppm ·	Up to 26 ppm ¹ Q1200 technology (2400 x 600 dpi	onality)	Op to 30 ppm	
rst-page-out Time (A4 SEF) (from ready mode)		0,010	8.5 second or less	quanty		
/arm-up Time			9 seconds or less (from sleep mode			
Memory	32MB	32 MB	64 MB	64MB	64 MB	
rocessor DL	1		266 MHZ		PCL6, Postscript®3™ Emul	
DL	PCL6, Host-Based	PCL6, Host-Based	PCL6, Host-Based	PCL6, Host-Based	Host-Based	
olour Touchscreen	_	_	-	_	2.7" Colour Touchscree	
onnectivity	10 Base-T/100Base-TX Ethernet		Wireless, 10 Base-T/100Base-	TY Ethernet TISB2 () Hi-Speed		
	USB2.0 Hi-Speed	ADIDA/A . ID) MINIC/N IDIOC			D D 1/D 10400 IDD	
letwork protocol for models with etwork function	IPv4: ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), WINS/NetBIOS name resolution, DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port 9100, IPP, F Server, SNMPv1/v2c/v3, HTTP Server, TFTP Client and Server, SMTP Client, ICMP, Web Services (Print) IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/ Port 9100, IPP, FTP Server, SNMPv1/v2c/v3, HTTP Server, TFTP Client and Server, St Client, ICMPv6, Web Services (Print) AirPrint, Google Cloud Print, FX Print Utility for iOS and Android					
Mobile Print upported Operating System	Windows Vista®, Windows® 7, Windows® 8, Windows Server 2003, Windows Server 2003 x64 Edition, Windows Server 2008, Windows Server 2008 R. Windows Server 2012, Windows Server 2012 R2®, Mac OS X v, 10.7.5, 10.8.x, 10.9.x³					
Ouplex Printing nput Paper Size (Paper Tray) Media Input Capacity (Paper Tray)	Automatic A4 SEF, Letter SEF, A5 SEF/LEF, A6 SEF, Executive SEF, Folio (8.5" x 13") SEF, Legal SEF, 16K(China only), 210x270mm (Taiwan only) 250 sheets 80qsm					
Media Input Capacity (manual feed slot)			1 sheet			
nput Paper Size (Manual Feed slot)	Width 76.2-216 mm, Length 127-355.6mm					
Media Output Capacity Media Types (Main Tray, or Duplex)		100 sheets 80gsm (Face down), 1 sheet (Face up with rear cover open) Plain paper, Recycled paper				
Media Types (Manual Feed slot)		Plain naner Thin Pane	r, Thick Paper, Recycled paper, label	envelope, bond paper		
nput Paper Weight (Paper Tray)			60 to 105 gsm			
nput Paper Weight (Manual Feed slot)			60 to 163 gsm			
utomatic Document Feeder	_			Up to 35 sheets (64-90 gsm)	V	
ingle pass Duplex Automatic Document Feeder Monthly Maximum Duty Cycle			- 10K pages		Yes	
Machine Life		5	OK page (Duplex 25k page) or 5 yea	rs		
rint Features	Toner Save Mode, N-up(2,4,9,16	or 25)4, Poster5(4,9,16,25), Heade	r/Footer5(time & date and/or user II	D), Watermarks ⁵ , manual duplex p	rinting ⁵ , manual booklet prin	
imensions (WxDxH)	356 x 360	x 186 mm	409 x 398.5 x 316.5 mm	409 x 398.5	5 x 316.5 mm	
/eight (without supplies)	5.9	kg	10.7 kg	11.1 kg	11.5 kg	
perating Environment Temperature umidity			e: 0° C to 40° C, Operating: 10° C to ronment: 20% to 80% RH (without			
coustics: Sound Pressure level	Printing: 50 dB(A)	Printing: 51 dB(A)	Printing:	50 dB(A)	Printing: 51 dB(A)	
lectrical Power		-	220-240 VAC, 50/60 Hz			
ower consumption ¹⁰	Ready/Standby: 58W ENERGY STAR® qualified	Ready/Standby: 58W ENERGY STAR® qualified	Ready/Standby: 60W ENERGY STAR® qualified	Ready/Sto	andby: 60W	
FCl			ENERGY STAR® qualified 1.2 k Wh/w	ENERGY ST 1.2 k Wh/w	AR® qualified 1.4 k Wh/w	
EC value	1.0 k Wh/w	1.2 k Wh/w	I.Z K Wh/W	1.2 K Wh/W	1.4 K Wh/W	
Vireless Specification Vireless LAN	_		IEEE <u>802.11b/g/n (Infra</u>	structure/Ad-hoc Modo)		
vireless LAN Vireless Network Security			. IEEE <u>802.11b/g/n (Infra</u> WEP 64/128 bit, WPA-PSK(TKIP/AFS). WPA2-PSK(AFS)		
letwork security (Wireless)	_		SMTP-AUTI	H, SNMP v3		
Vireless Certification	_	Wi-Fi Certification Ma	k License (WPA/WPA2-Personal), W	i-Fi Protected Setup (WPS) Identif	ier Mark Licensee, AOSS	
			Logo, Wi-Fi	CERTIFIED		
opy Function			11	6 1	11 . 20 1	
opy Speed (A4) opy Resolution	_	<u>_</u>	Up to 2	6 cpm ¹ Up to 600 x 600 dpi	Up to 30 cpm ¹	
irst-copy-out Time	_		Flat Bed	:10 seconds or less; ADF : 11 secon	nds or less	
eduction / Enlargement	-	_	ridebed	25 - 400% in 1% increments	103 01 1033	
1ulti-Copy	-	_		Up to 99		
opy Feature	_			y, N in 1 copying (N=2,4), sort(up		
utomatic 2-sided copy	_		_		Standard	
can Function				Colour CIC		
ype	- 1		I .	Colour CIS		
utomatic 2-sided scan	_		_		Standard	
	-	-	– Optical :(Scanner Gla	- ss) up to 600 x 1200 dpi (mana) 4	Standard 600x2400 dpi (colour)	
		-	– Optical :(Scanner Gla E	– ss) up to 600 x 1200 dpi (mono), i nhanced: up to 19,200 x 19,200 d	600x2400 dpi (colour)	
		-	E		600x2400 dpi (colour) Ipi	
canning Resolution		-	E Optical	nhanced: up to 19,200 x 19,200 d	600x2400 dpi (colour) lpi o/colour)	
canning Resolution can Depth	-	-	Optical (nhanced: up to 19,200 x 19,200 d : (ADF) up to 600 x 600 dpi (mon Colour 24 bit, Mono 8bit Gray Scal Platen: max 215.9mm x 300mm	600x2400 dpi (colour) lpi o/colour) le	
canning Resolution can Depth locument Size	-	-	E Optical ADF: max Wid	nhanced: up to 19,200 x 19,200 d : (ADF) up to 600 x 600 dpi (mon Colour 24 bit, Mono 8bit Gray Scal Platen: max 215.9mm x 300mm th 147.3 – 215.9mm x Length 14:	600x2400 dpi (colour) lpi o/colour) le 7.3 – 355.6mm	
canning Resolution can Depth locument Size	-	-	E Optical ADF: max Wid	nhanced: up to 19,200 x 19,200 d : (ADF) up to 600 x 600 dpi (mon Colour 24 bit, Mono 8bit Gray Scal Platen: max 215,9mm x 300mm th 147.3 – 215,9mm x Length 14 plication (Email, Image, File) by C	600x2400 dpi (colour) lpi o/colour) le 7.3 – 355.6mm	
canning Resolution can Depth ocument Size can Destinations	- - - -	-	ADF: max Wid	nhanced: up to 19,200 x 19,200 d (ADF) up to 600 x 600 dpi (mon Colour 24 bit, Mono 8bit Gray Scal Platen: max 215.9mm x 300mm th 147.3 – 215.9mm x Length 14: plication (Email, Image, File) by C M265 z only: Scan to FTP	600x2400 dpi (colour) ipi o/colour) ie 7.3 – 355.6mm ControlCenter utility	
canning Resolution can Depth ocument Size can Destinations	- - -	-	ADF: max Wid Scan to PC and ap Windows®: TWAIN, WIA fi	nhanced: up to 19,200 x 19,200 d : (ADF) up to 600 x 600 dpi (mon Colour 24 bit, Mono 8bit Gray Scal Platen: max 215,9mm x 300mm th 147.3 – 215,9mm x Length 14 plication (Email, Image, File) by C	600x2400 dpi (colour) ipi o/colour) de 7.3 – 355.6mm ControlCenter utility	
canning Resolution can Depth ocument Size can Destinations upported Driver	- - - -	-	ADF: max Wid Scan to PC and ap Windows®: TWAIN, WIA fi	nhanced: up to 19,200 x 19,200 d (ADF) up to 600 x 600 dpi (mon colour 24 bit, Mono 8bit Gray Scal Platen: max 215,9mm x 300mm th 147.3 – 215,9mm x Length 14: plication (Email, Image, File) by C M265 z only: Scan to FIP or Windows % TM	600x2400 dpi (colour) ipi o/colour) de 7.3 – 355.6mm ControlCenter utility	
can Depth ocument Size can Destinations upported Driver ax Function ompatibility	- - - -	-	ADF: max Wid Scan to PC and ap Windows®: TWAIN, WIA fi	nhanced: up to 19,200 x 19,200 d (ADF) up to 600 x 600 dpi (mon colour 24 bit, Mono 8bit Gray Scal Platen: max 215,9mm x 300mm th 147.3 – 215,9mm x Length 14: plication (Email, Image, File) by C M265 z only: Scan to F IP or Windows Vista®Windows® 7M TWAIN, ICA for OS 10.7.5/10.8.x/	600x2400 dpi (colour) ipi o/colour) le 7.3 – 355.6mm ControlCenter utility /indows® 8 /Windows® 8 .1 10.9.x Super G3	
canning Resolution can Depth ocument Size can Destinations upported Driver ax Function ompatibility ommunication System	- - - -	-	ADF: max Wid Scan to PC and ap Windows®: TWAIN, WIA fi	nhanced: up to 19,200 x 19,200 d (ADF) up to 600 x 600 dpi (more) Clour 24 bit, Mono 8bit Gray Scal Platen: max 215.9mm x 300mm th 147.3 – 215.9mm x length 14. M265 z only: Scan to FTP or Windows Vista® Windows® 7/M TWAIN, ICA for OS 10.7.5/10.8.x/	600x2400 dpi (colour) lpi o/colour) le 7.3 – 355.6mm .ontrolCenter utility /indows® 8 /Windows® 8.1 10.9.x Super G3	
canning Resolution can Depth ocument Size can Destinations upported Driver ox Function ompatibility ompatibility odem Speed	- - - - -	- - - - -	ADF: max Wid Scan to PC and ap Windows®: TWAIN, WIA f Mac:	nhanced: up to 19,200 x 19,200 d; (ADF) up to 600 x 600 dpi (mon Colour 24 bit, Mono 8bit Gray Scal Platen: max 215.9mm x 300mm th 147.3 – 215.9mm x length 14 (M25 z only: Scan to FTP or Windows Vista® Windows 7TWAIN, ICA for OS 10.7.5/10.8.x/	500x2400 dpi (colour) pipi pipi	
can Depth ocument Size can Destinations upported Driver ax Function ompatibility ommunication System lodem Speed lemory Transmission	- - - - -	- - - - - -	ADF: max Wid Scan to PC and ap Windows®: TWAIN, WIA f Mac:	nhanced: up to 19,200 x 19,200 d (ADF) up to 600 x 600 dpi (mon Colour 24 bit, Mono 8bit Gray Scal Platen: max 215,9mm x 300mm th 147.3 – 215,9mm x 14,0mt 11,0mt M265 z only: Scan to FTP or Windows Vista® Windows® 7M TWAIN, ICA for OS 10.7.5/10.8.x/ ITU-T P: 3.36. Up to 5'	600x2400 dpi (colour) pi o/colour) le 7.3 – 355.6mm ControlCenter utility /indows® 8 /Windows® 8.1 10.9.x Super G3 STN 5 kbps 00 pages²	
canning Resolution can Depth ocument Size can Destinations upported Driver ax Function ompatibility ommunication System lodem Speed lemory Transmission ut-of-paper reception	- - - - - - -	- - - - -	ADF: max Wid Scan to PC and ap Windows®: TWAIN, WIA fi Mac:	nhanced: up to 19,200 x 19,200 d (ADF) up to 600 x 600 dpi (mox 215.9mm x 300mm th 147.3 – 215.9mm x 1600 th 147.0 th	600x2400 dpi (colour) (pi o/colour) le 7.3 – 355.6mm ControlCenter utility //indows® 8 /Windows® 8 .1 10.9.x SIN 5 Kbps 00 pages² 00 pages²	
canning Resolution can Depth ocument Size can Destinations upported Driver ax Function ompatibility ommunication System todem Speed Ilemory Transmission ut-of-paper reception ax Resolution	- - - - -	- - - - - - -	ADF: max Wid Scan to PC and ap Windows®: TWAIN, WIA f Mac:	nhanced: up to 19,200 x 19,200 d (ADF) up to 600 x 600 dpi (mon Colour 24 bit, Mono 8bit Gray Scal Platen: max 215,9mm x 300mm th 147.3 – 215,9mm x Length 14; plication (Email, Image, File) by C M265 z only: Scan to F IP or Windows Vista®Windows® 7M TWAIN, ICA for OS 10.7.5/10.8.x/ ITU-T: P: 9: 33.6 Up to 5: Supeffine 8do/fr	600x2400 dpi (colour) (pi o/colour) (le 7.3 – 355.6mm ControlCenter utility /indows® 8 /Windows® 8.1 10.9.x Super G3 STN 5 kbps 00 pages²	
canning Resolution can Depth locument Size can Destinations upported Driver ax Function ompatibility ommunication System lodem Speed lemory Transmission lut-of-paper reception ax Resolution peed Dials	- - - - - - - - - -	- - - - - - - - -	ADF: max Wid Scan to PC and ap Windows®: TWAIN, WIA fi Mac:	nhanced: up to 19,200 x 19,200 d (ADF) up to 600 x 600 dpi (mon Colour 24 bit, Mono 8bit Gray Scal Platen: max 215,9mm x 300mm th 147.3 — 215,9mm x 100mm th 147.3 — 215,9mm x Length 14: plication (Email, Image, File) by C M265 z only: Scan to FTP or Windows Wista® Windows® 7/M TWAIN, ICA for OS 10.7.5/10.8.x/ ITU-T: 93.6 Up to 5: Superfine 8dot/r Up to 258 locations	500x2400 dpi (colour) lpi o/colour) le 7.3 – 355.6mm controlCenter utility /indows® 8 /Windows® 8 .1 10.9.x Super G3 STIN SIKDS O0 pages² O0 pages² on x15.4line/mm 0 locations Up to 250 locations	
canning Resolution can Depth locument Size can Destinations upported Driver ax Function ompatibility ommunication System lodem Speed lemory Transmission ut-of-paper reception ax Resolution peed Dials loadcasting loadcasting ax Features	- - - - - - - - - - -	- - - - - - - - - -	ADF: max Wid Scan to PC and ap Windows®: TWAIN, WIA for Mac:	nhanced: up to 19,200 x 19,200 d (ADF) up to 600 x 600 dpi (mon Colour 24 bit, Mono 8bit Gray Scal Platen: max 215,9mm x 300mm th 147.3 — 215,9mm x 100mm th 147.3 — 215,9mm x Length 14: plication (Email, Image, File) by C M265 z only: Scan to FTP or Windows Wista® Windows® 7/M TWAIN, ICA for OS 10.7.5/10.8.x/ ITU-T: 93.6 Up to 5: Superfine 8dot/r Up to 258 locations	600x2400 dpi (colour) lpi o/colour) le 7.3 – 355.6mm .ontrolCenter utility /indows® 8 /Windows® 8 .1 10.9.x SIN SIN SiNper G3 SIN O0 pages² 000 pages² 010 pages² 010 locations	
canning Resolution can Depth focument Size can Destinations upported Driver ax Function ompatibility ommunication System flodem Speed flemory Transmission ut-of-paper reception ax Resolution peed Dials roadcasting ax Features andset	- - - - - - - - - - - - - -	- - - - - - - - - - - - -	ADF: max Wid Scan to PC and ap Windows®: TWAIN, WIA fi Mac:	nhanced: up to 19,200 x 19,200 d (ADF) up to 600 x 600 dp (mo Clour 24 bit, Mono 8bit Gray Scal Platen: max 215,9mm x 300mm th 147,3 – 215,9mm x Length 14 M265 z only: Scan to FTP or Windows Vista®/Windows* 7/M TWAIN, ICA for OS 10.7.5/10.8.x/ 1TU-T: PS 3.36,6 Up to 5: Superfine 8dolfr Up to 258 locations PC Fax Senc	500x2400 dpi (colour) lpi o/colour) le 7.3 – 355.6mm controlCenter utility /indows® 8 /Windows® 8 .1 10.9.x Super G3 STIN SIKDS O0 pages² O0 pages² on x15.4line/mm 0 locations Up to 250 locations	
canning Resolution can Depth focument Size can Destinations upported Driver ax Function ompatibility ommunication System flodem Speed flemory Transmission ut-of-paper reception ax Resolution peed Dials roadcasting ax Features andset	- - - - - - - - - - - - - - - -	- - - - - - - - - - - - -	ADF: max Wid Scan to PC and ap Windows®: TWAIN, WIA f Mac:	nhanced: up to 19,200 x 19,200 d (ADF) up to 600 x 600 dp (mo Clour 24 bit, Mono 8bit Gray Scal Platen: max 215,9mm x 300mm th 147,3 – 215,9mm x Length 14 M265 z only: Scan to FTP or Windows Vista®/Windows* 7/M TWAIN, ICA for OS 10.7.5/10.8.x/ 1TU-T: PS 3.36,6 Up to 5: Superfine 8dolfr Up to 258 locations PC Fax Senc	500x2400 dpi (colour) lpi o/colour) le 7.3 – 355.6mm controlCenter utility /indows® 8 /Windows® 8 .1 10.9.x Super G3 STIN SKbps 00 pages² 00 pages² mm x 15.4line/mm 0 locations Up to 250 locations	
can Depth ocument Size can Destinations upported Driver ax Function ompatibility ommunication System todem Speed lemory Transmission ut-of-paper reception ax Resolution peed Dials roadcasting ax Features andset //arranty	- - - - - - - - - - - - - - - -	- - - - - - - - - - - - -	ADF: max Wid Scan to PC and ap Windows®: TWAIN, WIA fi Mac:	nhanced: up to 19,200 x 19,200 d (ADF) up to 600 x 600 dp (mo Clour 24 bit, Mono 8bit Gray Scal Platen: max 215,9mm x 300mm th 147,3 – 215,9mm x Length 14 M265 z only: Scan to FTP or Windows Vista®/Windows* 7/M TWAIN, ICA for OS 10.7.5/10.8.x/ 1TU-T: PS 3.36,6 Up to 5: Superfine 8dolfr Up to 258 locations PC Fax Senc	500x2400 dpi (colour) lpi o/colour) le 7.3 – 355.6mm controlCenter utility /indows® 8 /Windows® 8 .1 10.9.x Super G3 STIN SIKDS O0 pages² O0 pages² on x15.4line/mm 0 locations Up to 250 locations	
canning Resolution can Depth ocument Size can Destinations upported Driver ax Function ompatibility ommunication System lodem Speed lemory Transmission ut-of-paper reception ax Resolution beed Dials loadcasting ax Features andset larranty onsumables	- - - - - - - - - - - - - - - -	- - - - - - - - - - - - - -	ADF: max Wid Scan to PC and ap Windows®: TWAIN, WIA fi Mac:	nhanced: up to 19,200 x 19,200 d (ADF) up to 600 x 600 dp (mo Clour 24 bit, Mono 8bit Gray Scal Platen: max 215,9mm x 300mm th 147,3 – 215,9mm x Length 14 M265 z only: Scan to FTP or Windows Vista®/Windows® 7/M TWAIN, ICA for OS 10.7.5/10.8.x/ 1TU-T: Pi 33,6 Up to 5: Superfine 8dolfr Up to 258 locations PC Fax Senc	500x2400 dpi (colour) lpi o/colour) le 7.3 – 355.6mm controlCenter utility /indows® 8 /Windows® 8 .1 10.9.x Super G3 STIN SKbps 00 pages² 00 pages² mm x 15.4line/mm 0 locations Up to 250 locations	
canning Resolution can Depth locument Size can Destinations upported Driver ax Function compatibility communication System loddem Speed lemory Transmission lout-of-paper reception lox Resolution peed Dials roadcasting ax Features landset loadset loa	- - - - - - - - - - - - - - - -	- - - - - - - - - - - - - -	ADF: max Wid Scan to PC and ap Windows®: TWAIN, WIA fi Mac:	nhanced: up to 19,200 x 19,200 d (ADF) up to 600 x 600 dp (mo Clour 24 bit, Mono 8bit Gray Scal Platen: max 215,9mm x 300mm th 147,3 – 215,9mm x Length 14 M265 z only: Scan to FTP or Windows Vista®/Windows® 7/M TWAIN, ICA for OS 10.7.5/10.8.x/ 1TU-T: Pi 33,6 Up to 5: Superfine 8dolfr Up to 258 locations PC Fax Senc	500x2400 dpi (colour) lpi o/colour) le 7.3 – 355.6mm controlCenter utility /indows® 8 /Windows® 8 .1 10.9.x Super G3 STIN SKbps 00 pages² 00 pages² mm x 15.4line/mm 0 locations Up to 250 locations	
Automatic 2-sided scan icanning Resolution ican Depth Document Size ican Destinations supported Driver ax Function compatibility communication System Modern Speed Memory Transmission Dut-of-paper reception ax Resolution ippeed Dials froadcasting fox Features landset Warranty Consumables hipped consumables (approx.) itandard Capacity Toner cartridge (approx.) ⁸ lidiph Capacity Toner cartridge (approx.) ⁸ lidiph Capacity Toner cartridge (approx.) ⁸	- - - - - - - - - - - - - - - -	- - - - - - - - - - - - - -	ADF: max Wid Scan to PC and ap Windows®: TWAIN, WIA fi Mac:	nhanced: up to 19,200 x 19,200 d (ADF) up to 600 x 600 dp (mo Clour 24 bit, Mono 8bit Gray Scal Platen: max 215,9mm x 300mm th 147,3 – 215,9mm x Length 14 M265 z only: Scan to FTP or Windows Vista®/Windows® 7/M TWAIN, ICA for OS 10.7.5/10.8.x/ 1TU-T: Pi 33,6 Up to 5: Superfine 8dolfr Up to 258 locations PC Fax Senc	500x2400 dpi (colour) lpi o/colour) le 7.3 – 355.6mm controlCenter utility /indows® 8 /Windows® 8 .1 10.9.x Super G3 STIN SKbps 00 pages² 00 pages² mm x 15.4line/mm 0 locations Up to 250 locations	

Print/copy speed may decrease due to factors such as paper type, paper size, and printing conditions. ² Measured diagonally. ³ Mac drivers are available by web download. ⁴ N-up for Mac (2,4,6,9, or 16). ³ Windows Only. ⁴ Max 1200 x 1200 dpi scanning with WIS (Windows Image Acquisition) driver in Windows Vista, Windows 7 and Windows 8. ³ ITU-T Test Chart, Standard resolution. ⁵ Declared yield in accordance with ISO/IEC 1975.2 Yield will vary based on image area coverage and print mode. ⁵ Drum yield may vary by the type of use. ¹⁰ Measured when the anothine is connected to the USB interface. This product has been tested and found to comply with the Class 1 Laser Equipment requirements defined by the international standard IEC60825-1:2007 and has no light exposure hazard. The product has no hazardous light emission as it features light protection components and covers to shut in all light beam during operation and maintenance. Internal Laser radiation. Wave length: 770 - 800 nm. Output: 25 mW max. Laser Class: Class 3B. [^]Replacement unit will be shipped to either customer location or the nearest service provider.

Reproduction Prohibitions Please note that reproduction of the following is prohibited by law:
Domestic and foreign currencies, government-issued securities, and national bonds and local bond certificates. Unused postage stamps, post cards, etc. Certificate stamps stipulated by law. Reproducing works forming the subject matter of copyright (literary works, musical works, paintings, engravings, maps, cinematographic works, drawings, photographic works, etc.) is not permitted unless the reproduction is for the purpose of personal use, family use or other similar uses within a limited circle.

















For Your Safety
Before using the product, read the Instruction Manual carefully
for proper use. Use the product with the power source and voltage
specified. Be sure to establish ground connection. Otherwise,
electronic shock may result in the case of a failure or short circuit.

For more information or detailed product specification, please call or visit us at

Fuji Xerox Asia Pacific Pte Ltd

14a Rodborough Road Frenchs Forest NSW 2086 Australia 1300 793 769 | www.fujixeroxprinters.com.au New Zealand 0800 993 769 | www.fujixeroxprinters.co.nz

